




CANIS GO 410


The CANIS GO 410 LED work lamp offers a quality solution with low power consumption. The light is suitable for mounting in tight places and for applications in demanding working environments.

Light patterns

Canis Go 410 1000lm
Wide Flood



Canis Go 410 1000lm
Flood




NORDICLIGHTS



Features

-  Long Lifetime
-  Low Maintenance
-  Waterproof
-  Heavy Duty Construction
-  Reverse Voltage
-  EMC
-  Load Dump Protected
-  Over Voltage Protected
-  Overheat Protected
-  Salt Mist
-  Optically Even Light
-  Multi Voltage
-  Compact

Drawings



Specifications

Theoretical Lumens Output:	1600lm
Operational Lumens Output:	1000lm
Colour Temperature:	5000K
Nominal / Input Voltage DC:	12/2 9-16V / 18-32V
Power Consumption:	16W
Nominal Current at:	24V 0.60A 12V 1.05A
Connector:	Built-in Deutch 2-pin
Mount:	Single Bolt M8
Shock:	60G
Vibration:	8Grms 24-2000Hz
Lens:	PA
Body:	Aluminium
Weight:	0.5kg
IP Rating:	IP68 IP6K9K
Salt Mist:	ISO 9227 240H
EMC:	CISPR 25 Class 5 EN12895 ISO 13766 ISO 14982 ISO 7637-2
Operating Temperatures:	-40°C... +85°C (Overheat protected)

Nordic Lights™

Herrmans Oy Ab

P.O. Box 36, Bennäsvägen 143
FIN-68601 Jakobstad, FINLAND

Tel: +358 (0)6 781 5100

Fax: +358 (0)6 723 3160

E-mail: nordiclights@nordiclights.com

Web: www.nordiclights.com

VAT ID: FI17390930