Scotsman®
Ice Systems

HID312

Other models in this range:
HID 525 - HID 540

Ice and water dispenser up to 110 kg

Shown with optional KLP24A legs

Features

Smarter Construction - Durable stainless steel evaporator and exterior panels. Greaseless bearings for reduced maintenance. Larger sink opening and dispensing area. Antimicrobial AquaArmor with AgION is molded into key components.

Space maximizing design - The industry's smallest operational footprint relative to capacity. Featuring specially designed contoured sides for ehanced breathability and an external air filter.

More convenient front access - Removable front panels allow ease of access and service to all key internal components. Including removable storage bn for better cleaning and maintenance access.

Enhanced service features - Intuitive LED diagnostic lights reduce service time. Unit specific QR code for quick access to service manuals and warranty history. Convenient USB drive that allows for fast software updates. New removable sink and grill provide maximum access for ease of cleaning.

Energy and Water Efficiency - Industry leading efficiencies deliver deliver on going savings.

Quieter operation - Improved condenser fan function.

Technologies

Total Hygiene Concept · Energy Saving · agion

	+C° / -C°	24h 21°C : 10°C [kg]	[lb]	32°C : 21°C [kg]	[lb]	[kg]	[lb]
HID 312 AS		110	242	91	200	5	11

[V/Hz/ph]
220-240/50/1

R134a

D W H

[WxDxH mm]
415 x 619 x 886

[WxDxH inches]
16.36"x 24.38"x 35"

This product qualifies for the following listings:

CE NSF

Certified ISO 9001:2008

Chewable, slow-melting ice that allows for more reliable dispensing.

19 mm x 8 mm x 9,5 mm
(3/4" x 5/16" x 3/8")

2 Years Warranty
Subject to certain limitations and exclusions

DOWNLOAD
Apple store
Google play
Windows store

www.scotsman-ice.it
www.scotsman-ice.com

1/2016

Scotsman
Ice Systems

HID312

Other models in this range:
HID525

Ice and water dispenser up to 110 kg



All models include 7.5' power cord with NEMA 5-15P plug

Installation Note: Allow 6" space at left, back and right side for ventilation and utility connections.

Minimum		Maximum
10°C (50°F)		38°C (100°F)
5°C (40°F)		38°C (95°F)
-10%		+10%
1,4 bar 20 psi		5,5 bar 80 psi

	+C° -C°	[Btu/h]	[W]	[Ømm²]	[W]	FUSE	[kWh] - 100 kg	[l/h]	32°C 90°F 21°C 70°F [gal/h]	[kg]	[lb]
HID 312 AS		3200	938	3x1,5	420	15 A	11	3,8	1,0	83	183

IMPORTANT NOTICE:
Models and specifications are subject to change without notice.
This spec sheet is meant for commercial purpose only.
For technical documentation please refer to our service manuals.

www.scotsman-ice.it
www.scotsman-ice.com

Scotsman
Ice Systems

Milano Madrid Chicago Dubai Singapore Shanghai Johannesburg

1/2016