

Single Color HD-E6x LAN LED Controller Parameter

Type	HD-E62	HD-E63	HD-E64	HD-E66
Ranges	1024*64, 2048*32	1024*128,3072*32	1024*256,2048*64	2048*512
Output	2*HUB08+4*HUB12	4*HUB08+8*HUB12	1*HUB50PIN	2*HUB50PIN
Memory	8M byte			
Comunication	U-Disk & LAN			U-Disk & LAN & RS232
Scan	Static - 1/16scan			
7color	√	√	√	√
Programs	Max 1000 Programs, Can play by time section or control by buttoms			
Regions	Max 20 regions,support regions overlap.			
Content	Text/Picture/Timing/Animation/3D Text/EXCEL/SWF/Temperature			
Control	Can play by time section or control by buttoms/remoter			
Effects	More then 40 effects and image background, shaped boder.			
Cross screen	√	√	√	√
Extention	Temprature/Humidity/IR Remoter/3buttoms for Program control			
Auto shutdown	√	√	√	√
Brightness	By Time section / By Sensor			
Environment	Voltage : 4.2V-5.5V , Temperature : -20°C~ 80°C, Consumption<0.5W			
Special Fuctions	1.First 3D text effect in all LED trades. 2.Support regions overlap. 3.Support Graylevel ; regions background, smart setting ; 4.Support buttom counter up/down, buttom timer, realtime region ; 5.Support text rotation, 90°,180°and 270° ; 6.Auto IP Setting, Support connect to router & exchanger			

HUB Define

