

HD-A30/A30+ Full color LED Controller Parameter

Model	HD-A30	HD-A30+
Range	1024*512,512*1024	1024*512,3840*136,256*2048
Output	2*HUB50pin	No HUB
Memory	4G Byte on board, (U-disk expend supported)	
Communication	U+Disk & LAN / Wifi,3G,4G(need buy Module)	
Scan Mode	Static - 1/32scan, support smartsetting	
Gray Level	256 ~ 65535 graylevel	
Programs	No limit, Can play by time section	
Regions	No limit, support regions overlap, regions transparent	
Content	Video/Text/Picture/Time/3D Text/Animation/Office/SWF	
Video type	AVI,WMV,RMVB,MP4,MPG,FLV,SWF,VOB,etc...	
Effects	More then 40 effects and image background, shaped boder.	
Hardware decode	√	√
Exepention	Temperature/Humidity/IR Remoter/Brightness sensor	
Audio	√	√
Brightness	By Time section / By Sensor	
Evironment	Voltage : 4V-6V , Temperature : -20°C~ 80°C, Consumption<5W	
Special Functions	1.Made for small spacing LED screen.Advertisement machines 2.A30 is Sending & Receiving card together, A30+ is Only Sending Card 3.Hardware decoder, better video view. 4.Support 3G/4G/Wi-Fi Internet management. ; 5.Support Cascade receiving cards; 6.Screen rotation, 90°、180° or 270° ; 7.Auto IP setting, Support router connection.	
HUB Define	<p style="text-align: center;">50PIN</p>	