

HD-A60x Full color Dual mode LED Controller Parameter

Model	HD-A601	HD-A602	HD-A603
Range	800*600,3840*124,234*2048	1280*720,3840*240,450*2048	1920*1080,3840*540,1012*2048
Output	CAT6 LAN	CAT6 LAN	CAT6 LAN
Memory	4G Byte on board, (U-disk expend supported)		
Communication	U+Disk & LAN / Wifi,3G,4G(need buy Module)		
Scan Mode	Static - 1/32scan, support smartsetting		
Gray Level	256 ~ 65535 graylevel		
Programs	No limit, Can play by time section		
Regions	No limit, support regions overlap, regions transparent		
Content	Video/Text/Picture/Time/ 3D Text /Office/SWF		
Video type	AVI,WMV,RMVB,MP4,MPG,FLV,SWF,VOB,etc...		
Effects	More then 40 effects and image background, shaped boder.		
Hardware decod	√	√	√
Audio	√	√	√
Brightness	By Time section / By Sensor		
Environment	Voltage : 4V-6V , Temperature : -20°C ~ 80°C, Consumption<5W		
Special Functions	1.Online-Offline Dual mode, Auto change mode. 2.Hardware decoder, better video view. 3.Support 3G/4G/Wi-Fi Internet management. ; 4.Support Cascade receiving cards, C10C have 10*HUB75 ; 5.Screen rotation, 90°、180°or 270° ; 6.Auto IP setting, Support router connection.		