

# SRP-350III

3 inch POS printer



Retail



Restaurants & Bars




Ticketing



Kiosk

# The Industry's steady seller




### Powerful Printing Performance

- Fast printing up to 250mm/sec (25% faster than the SRP-350II)
- 4-type dithering options for graphic printing
- A family of the world-class SRP-350 line



### Multiple interface choice

- Built-in USB with a choice of Serial, Parallel, or Ethernet



### User-friendly Design

- Anti-jam guide
- Stand-alone or Space-saving wall-mount use
- 2" or 3" paper choice

# SRP-350III

## 3 inch POS printer

### Specifications

#### Print Characteristics

**Print Method**

Direct Thermal

**Print Speed**

SRP-350III: Up to 250 mm/sec  
SRP-352III: Up to 230 mm/sec

**Print Resolution**

SRP-350III: 180 dpi  
SRP-352III: 203 dpi

**Print Width**

Up to 72 mm

**Sensor**

Paper End, Paper Near End, Cover Open

#### Media Characteristics

**Media Type**

Receipt

**Media Width**

80 mm  
Optional 58 mm (N type)

**Media Roll Diameter**

Up to 83 mm

**Media Thickness**

0.05 ~ 0.08mm

**Supply Method**

Easy Paper Loading

#### Physical Characteristics

**Dimensions (W x D x H)**

145 x 204 x 146 mm  
(5.70 x 8.03 x 5.74 inch)

**Weight**

1.55kg (3.41 lbs.)

**Electrical**

EnergyStar Certified,  
External Power Adaptor 100-240V AV, 50/60Hz

**Drawer Port**

2 ports (via y-type adaptor)

#### Performance Characteristics

**NV Image Memory**

256 Kbytes (mono)

**Receive Buffer**

4 Kbytes

**User Define Buffer**

12 Kbytes

**Interface**

- ① USB V2.0 FS + Serial
- ② USB V2.0 FS + Parallel
- ③ USB V2.0 FS + Ethernet
- ④ USB V2.0 FS + SD

#### Environment Characteristics

**Temperature**

Operating: 0 ~ 40°C (32 ~ 104°F)  
Storage: -20 ~ 60°C (-4 ~ 140°F)

**Humidity**

Operating: 10 ~ 80% RH  
Storage: 10 ~ 90% RH

#### Reliability

**Thermal Print Head (TPH)**

150 km

**Auto Cutter**

1.8 Million Cuts

#### Software

**Emulation**

BXL / POS

**Driver / Utility**

Windows Driver, OPOS / JPOS Driver,  
Linux / Mac CUPS Driver,  
Virtual COM USB / Ethernet Driver,  
Utility Program

**SDK / Plugin**

Android / iOS / Windows SDK, Linux SDK,  
Xamarin SDK, Chrome SDK, Cordova Plugin

**Application**

mPrint App (iOS)

#### Fonts / Graphics / Symbologies

**Character Size**

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24  
KOR, CHN, JPN: 24 x 24

**Characters Per Line**

SRP-350III: Font A: 42 Font B, C: 56  
KOR, CHN, JPN: 21

SRP-352III: Font A: 48 Font B, C: 64  
KOR, CHN, JPN: 24

**Character Sets**

Alphanumeric: 95  
Extended Graphics: 128 x 33 page  
International: 32

**Graphics**

Supporting user-defined fonts, graphics,  
formats, and logos

**Barcode Symbologies**

1D: Codabar, Code 39, Code 93, Code 128,  
EAN-8, EAN-13, ITF, UPC-A, UPC-E  
2D: Data Matrix, PDF417, QR code

#### Accessories

**Optional**

Splash Proof Cover, External buzzer, B-Melodist,  
USB A-B Cable 1.8m



BR\_SRP-350III\_EN\_FEB20\_V1

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

**BIXOLON**

**BIXOLON Co., Ltd.**  
+82 (0) 31 218 5500  
sales@bixolon.com

**BIXOLON America Inc.**  
+1 858 764 4580  
sales@bixolonusa.com

**BIXOLON Europe GmbH**  
+49 211 68 78 54 0  
sales@bixolon.de

www.Bixolon.com