

## Product Data Sheet (2020-09-29)

### FixLock connection system with junction

FixLock set of threaded joints with T-piece junction for corrugated pipe connection without the need for tools with union (F) to any pipe system, scope of supply including 2 union nuts and 2 insert rings.



Type	Model [DN]	Connection			Weight [kg]	###	Order Code
		A ["]	B ["]	C ["]			
FixLock set T DN16	16	3/4" FL	1/2" F	3/4" FL	0,23	1	M90250.043FL
FixLock set T DN20	20	1" FL	3/4" F	1" FL	0,34	1	M90250.931FL
FixLock set T DN16	16	3/4" FL	3/4" FL	1/2" F	0,23	1	M90250.044FL
FixLock set T DN20	20	1" FL	1" FL	3/4" F	0,33	1	M90250.932FL



### Technical information

- operating temperature: 200 °C.
- Operating pressure: depending on dimension of corrugated pipe (up to DN25: 16 bar, DN32: 10 bar).
- DVGW-certified for the dimensions DN12 to DN20.
- Shaft-sealing (no seal necessary).

FixLock may only be used in conjunction with Inoflex stainless steel corrugated pipe due to the required production tolerances. (Otherwise the warranty is invalidated).

Flamco Group  
 Plotterweg 31  
 3821 BB, Amersfoort - nl  
 T +31 33 299 75 00  
 E [info@flamcogroup.com](mailto:info@flamcogroup.com)  
 I [flamcogroup.com](http://flamcogroup.com)