P145/EA160DLF

CONSTRUCTION VEHICLE E SEATS







	P145EA160DLF
Air suspension	A
Air suspension with 12V or 24V built-in com	pressor
Mechanical suspension	A
Weight adjustment	Automatic up to 150kgs
Suspension stroke	90mm
Height adjustment	60mm
Turn Table	A
Adjustable shock absorber	
Slide travel	190mm
Lumbar adjustment	A
Horizontal isolator	•
Adjustable foldable armrests	A
Adjustable headrest	•
Backrest adjustment	•
Seat cushion tilt adjustment	•
Seat cushion depth adjustment	•
Vinyl trim (cut&sew)	N/A
Cloth trim (cut&sew)	•
Vinyl trim (vacuum type)	▲ Order P170/CEA150D
Cloth trim (vacuum type)	▲ Order P170C/CEA150D
Genuine leather trim	N/A
3-point seat belt	N/A
2-point seat belt	
Document box-pouch	
Front Controls (except backrest recline har	ndle)
LH Controls	N/A
RH Controls	N/A
Heater	
Operator presence switch	
Slides between seat top and suspension	•
Standard connection widths	280mm
Optional connection widths	260mm(Order - / EA150D)
Testing 550 ±10	IS07096 EM3-EM4-EM6



