

ZK1515-C

All in One Biometric Smart POS Terminal



Features

- AMD A6-5345M@2.2G, Two core 2 Line processor;
- 15" Bezel-Free True-Flat PCAP touch screen;
- Optional Intel® Core™ i3 and i5 processor;
- Fingerprint verification makes transaction more safe;
- Modular design with aluminium alloy material;
- Dual hinge stand, table stand and standard VESA mount;
- VFD and second display can be adjusted in angle;
- Easy to hide cables and fanless design;

Optional



Magnetic Stripe
Card Reader



2nd LCD Display Screen



Barcode Scanner



Fanless Design



Thermal Printer



Wall Mounted



VFD Customer Display



Fingerprint Module

Specifications

Model Name	ZK1515-C
System	
Processor	AMD A6-5345M@2.2G, Two core 2 Line processor
Chipset	AMD Chipset
Graphics	AMD Radeon HD 8000
System Memory	4GB and support up to 16GB
Storage Device	SSD 128GBM.2
OS Supported	Windows 7, Windows 8, Windows 10 IoT Enterprise, POS Ready 7, Linux, Ubuntu 18.04 3 or higher (64 bit)
Audio	Realtek ALC662 with Integrated speakers
Display and Touch	
Type	15" TFTLCD, LED Backlight
Resolution	1024x768, 300 NITS minimum Display Brightness
Touch Screen	Projected Capacitive Touch Screen
Customer Display	LED (8C digital tube)
External I/O Ports	
VGA	1*DB-15
Ports	5*USB 2.0, 1*USB 3.0 & 1*PS2
COM	4
HDMI	1
LAN	1*RJ45
Audio	1*Line-in and 1*Line-out
Power	
Power Supply	90 - 130 Watts Power Supply
Physical Environment	
Operating Temperature	0 C ~ 50 C at 20% - 80% Humidity
Storage Temperature	20 C ~ 55 C at 20% - 80% Humidity
Dimensions (W*HxD)	228*385*403 mm
Certification	CE, FCC, BIS
Material	Aluminum alloys, ABS, Water and Dust Resistant design to protect liquid and dust damage (IP54)
Color	Black
Options & Peripherals	
2nd Display	8"/10" TFT LCD
Customer Display	20 Columns x 2 Lines
MSR	3 Tracks
Barcode Scanner	2D Barcode scanner
Fingerprint	USB fingerprint module

